8 **SPECIFICATION CONTROL DRAWING** Ø3.543 **OD** Ø3.275 ID REF С С 0.134 WALL THICKNESS D6025-XXX CROSSTUBE MATERIAL WHERE XXX IS LENGTH IN INCHES EG. 103" LONG TUBE: D6025-103 (C) 1) MATERIAL: 3.543 OD X 0.134 WALL 7075-T73/T73510/T73511 (WW-T-700/7 OR QQ-A-225/9 OR QQ-A-200/11 OR ASTM B210 OR ASTM B241) SEAMLESS ALUMINUM TUBE. MINIMUM ULTIMATE TENSILE STRENGTH = 66 KSI
MINIMUM YIELD TENSILE STRENGTH = 56 KSI
MINIMUM ELONGATION = 12%

2) FINISH: CHEMICAL CONVERSION COAT PER DART QSI 005 4.1 PRIOR TO SENDING THE
EXTRUSION TO AN OUTSIDE VENDOR

3) TOLERANCES: O.D.: +/- 0.008 MEAN (+/- 0.016 INCLUDING OVALITY)
WALL: +/-0.006 MEAN (+/- 0.013 INCLUDING ECCENTRICITY)
LENGTH: XXX +0.500/0.000 UPDATE MATERIAL PROPERTIES, TOLERANCES AND ADD CHEMICAL CONVERSION COAT ML 17.05.25 ADDED NOTE 9 17.01.20 **NEW ISSUE** Α 16.03.24 LENGTH: XXX +0.500/-0.000 REV. **DESCRIPTION** STRAIGHTNESS: 0.010" DEVIATION / 12" LENGTH DATE 4) UNITS: INCHES UNLESS OTHERWISE NOTED 5) BREAK SHARP EDGES: N/A **DESIGN** ML DART AEROSPACE LTD DRAWN ML HAWKESBURY, ONTARIO, CANADA 6) IDENTIFICATION: NONE 7) WEIGHT: N/A **CHECKED** AJS DRAWING NO. REV. C **APPROV** 8) EXTREME CARE MUST BE TAKEN TO PROTECT THE OUTSIDE SURFACE OF THE TUBE. D6025 MFG. APPR. LL SHEET 1 OF 1 THE OUTSIDE SURFACE MUST BE SMOOTH AND FREE FROM SURFACE DEFECTS SUCH AS **APPROVED** TITLE ECN 17-667 WM **SCALE** SCRATCHES, NICKS, OR DENTS. DEFECTS UP TO 0.005" MAY BE BLENDED OUT LONGITUDINALLY. CROSSTUBE MATERIAL CIRCUMFERENTIAL GRIND MARKS ARE UNACCEPTABLE. DE APPR. CP (// NTS COPYRIGHT © 2016 BY DART AEROSPACE LTD

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLED ON THE EXPRESS CONDITION THAT IT IS

NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT

WRITTEN PERMISSION FROM DART AEROSPACE LTD. DATE 17.05.25 8 3